



Computerized Guard Tour System

Model GOW07i

**Not like other basic patrol reader ,adopt contactless technique to download patrol data from patrol reader GOW07i*

**Without USB communication port enable reader more durable and water-proof*

**Completely sealed design and super metal tank make it strong to resist man-made damage*

**Flexible rubber coating shell, strong ability of anti-wrestling*

**Non-rechargeable battery, can be used continuously for 1 year*



Features

- Auto-induction, no need to press any button
- RFID inductive reading, workable for 125khz EM RFID tags
- Super waterproof and impact resistance with flexible rubber coating
- Contactless data downloading , without USB communication port on device body
- LED+beeps operation prompt

Specifications

- | | |
|------------------------------|---|
| ▪ Read Method: | RFID Auto- induction card reading |
| ▪ Storage Capacity: | 8000 Logs |
| ▪ Dimension: | 142 x 32 x 40mm |
| ▪ Net Weight: | 150g |
| ▪ Read Response: | <0.2S |
| ▪ Read Distance: | 1cm to 3cm |
| ▪ Direction: | LED + Beeps |
| ▪ Working Temperature: | -20°C to 70°C |
| ▪ Working Humidity: | 0% to 95% |
| ▪ Working Frequency: | 125KHZ |
| ▪ Standby Power Consumption: | 100uA |
| ▪ Work Power Consumption: | 8mA |
| ▪ Battery Life: | Continuous use around 1 years (Base on Usage) |
| ▪ Battery: | 3V Lithium battery(CR123A),non-rechargeable |
| ▪ Communication: | Wireless communication |
| ▪ Communication Baud Rate: | 57600Bps |

Accessories



Leather Holder



Wireless Comm. Station



Wireless Comm. Station
(Display, Battery & Memory)
(Optional)



ALL RIGHTS RESERVED

Authorized Dealer:

Blank area for authorized dealer information.