

BARCODE LASER SCANNER



Your Trusted Brand



For 1D Barcode



Wired

BS-1D BARCODE SCANNER

- Scan form : 650 mm Visible Laser Secondary Tube
- Reading Speed : 100 Times / Second
- Decode Range : UPC 13mil 3-31cm / CODE39 5mil 7-10cm
- Dimension : 174mm x 71.5mm x 92mm
- Interface : USB, RS232
- Power Consumption : 5V (Operating 57mA, Idle 37 mA)



For 1D Barcode



USB Wireless

BS-1DW BARCODE SCANNER

- Scan Form : 650 m Visible Laser Secondary Tube
- Reading Speed : 100 Times / Second
- Decode Range : UPC 13mil 3-31cm (CODE39 5mil 7-10cm)
- Dimension : 174mm x 71.5mm x 92mm
- Interface : USB
- Power Consumption : 5V
- Wireless Technology : 2.4GHZ
- Communication : 60m
- Battery Capacity : 1200MAH



For 1D & 2D
Barcode



Wired

BS-2D BARCODE SCANNER

- Resolution: 640 x 480
- FOV: Horizontal 40°, Vertical 34°
- Decode Range: UPC 13mil 3-22cm (CODE39 6.6mil 4-8cm)
- Aimer : Red LED
- Illumination : White LED
- Dimension : 165mm x 86mm x 66mm
- Interface : USB (HID-KBW), USB HID-POS
- Power Consumption : 5 VDC (Operating 210mA, Idle 70mA)



For 1D & 2D
Barcode



USB Wireless

BS-2DW BARCODE SCANNER

- Resolution : 640 x 480
- FOV : Horizontal 40°, Vertical 34°
- Decode Range : UPC 13mil 3-22cm (CODE39 6.6mil 4-8cm)
- Aimer : Red LED
- Illumination : White LED
- Dimension : 165mm* 86mm*66mm
- Interface: USB
- Power Consumption : 5VDC
- Wireless Technology : 2.4GHZ
- Transmission Distance : 60m
- Battery Capacity : 1800MAH

