

## TC-144

PROFESSIONAL FM TRANSCEIVER

## **Main Features**

Battery Save, CTCSS/DCS Voice Prompt 1500mAH Li-ion Battery Pack Power Output 3W





## **Main Features**

- 🛂 Battery Save, CTCSS/DCS
  - Voice Prompt
  - 1500mAH Li-ion Battery Pack
  - Power Output 3W

## **SPECIFICATION**

GENERAL		TRANS
Frequency Range	UHF: 400~480MHz	RF Powe
Operating Temperature	-20°C~+60°C	Modulat
Frequency Combination	Phase lock frequency synthesize	Max. Fre
Frequency Stability	±2.5ppm	Remain
Memory Channel	16 Channels	Transmi
Working voltage	DC 3.7V	RECEIV
Antenna Impedance	50Ω	Sensitiv
Operating Mode	Simplex of co-frequency or alien	Squelch
	frequency	Intermo
Dimension	97mm×57mm×30mm	Audio P
Weight	200g (Include Battery Pack)	Receivir
		Squelch

TRANSMIT PART					
RF Power	3W				
Modulate Mode (W/N)	16КФF3E,11КФF3E				
Max. Freq. Deviation (W/N)	<5K / <2.5KHz				
Remain Wave Radiation	<-60dB				
Transmitting Current	≤1300mA				
RECEIVE PART					
	<0.25µV(12dB SINAD)				
Sensitivity	<0.25µV(12dB SINAD)				
Sensitivity  Squelch Sensitivity	<0.25µV(12dB SINAD) <0.20µV				
•	·				
Squelch Sensitivity	-0.20μV				
Squelch Sensitivity Intermodulation Antijamming	<0.20µV 50dB				

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.