



# Q1

## Mynet Nationwide Coverage

Selective Call, Group Call and All Call  
 Ultra High Capacity Li-ion Battery  
 12V/24V Input Intelligent Charger  
 Network Signal Strength Prompt  
 Voice Prompt Authority Setting  
 GPS Function Optional



### DIGITAL PUBLIC NETWORK WALKIE-TALKIE



[www.motoplus.com.my](http://www.motoplus.com.my) | [www.mynet.com.my](http://www.mynet.com.my)



# Q1



### DIGITAL PUBLIC NETWORK WALKIE-TALKIE

Selective Call, Group Call and All Call  
 Ultra High Capacity Li-ion Battery  
 12V/24V Input Intelligent Charger  
 Network Signal Strength Prompt  
 Voice Prompt Authority Setting  
 GPS Function Optional

General Features	Dimensions (Without Antenna)	100mm x 58mm x 32mm	
	Weight (With Battery)	About 194g	
	Operating Temperature	-30°C to +75°C	
	Operating Voltage	DC 3.3V-4.2V (3.8V is recommended)	
	Operating Current	Peak Current	About 0.6A
Average Current		About 540mA@UMTS 2100	About 239mA@GSM 900
Standby Current		About 5mA@UMTS	About 5mA@GSM
Baseband	(U)SIM/SIMU	Standard SIM card interface 3V SIM card and 1.8V SIM card	
	USB Interface	USB 2.0 HIGH SPEED	
	UART Interface	8-wires UART	
	MAX. Power Consumption	About 2.2μW	
Radio Frequency	UMTS Band	HSDPA/WCDMA: 2100/1900/850(900)MHz	
	Transmit Power	UMTS 2100/1900/900/850: Power Class 3 (+24dBm +2.5/-1.5dBm)	
		EDGE 850MHz/900MHz: Power Class E2 (+27dBm +4.5/-1.5dBm) EDGE 1800MHz/1900MHz: Power Class E2 (+26dBm +4.5/-2.5dBm)	
Receiving Sensitivity	WCDMA2100: ≤-108dBm WCDMA1900: ≤-109dBm WCDMA900: ≤-109dBm WCDMA850: ≤-109 dBm		
	GSM850/900/1800/1900: ≤-107dBm		



[www.motoplus.com.my](http://www.motoplus.com.my)