

**K3**

## Infrared Thermometer Forehead

Accurate temperature measurement



**0.1S**

Quick Measurement

**±0.2**

High Accuracy



Alarm Function

**°C/°F**

°C/°F Unit Available



Energy Saving

**1W**

One Week Standby

**SPEED**

## **1s Quick Measurement**

non-contact, avoid cross-infection

**Accuracy**

**High Accuracy:  $\pm 0.2$  Degrees**

**Warning**

## **High Temperature Alarm**

Abnormal temperature: Flashing red lights and alarm 'DiDi'

**Energy saving**

## **One Week Standby**

Designed for continuous, long-term use

# Introduction



## Technical Data

Accuracy	±0.2 degrees	Response time	0.5s
Abnormal automatic alarm	flashing + "Di Di" sound	Charging method	USB charging or battery
Automatic measurement	measuring distance 5cm ~ 10cm	Input	USB DC 5V
Standby	About one week	Weight	350g
Install method	nail hook, double-sided adhesive sticking, bracket fixing	Dimensions	170*115*140mm
Operating temperature	10℃~40℃ (Recommend 15℃~35℃)	Infrared measuring range	0~50℃
Standby	5s (Red dot dynamic cycle)	Screen	Digital display



CE

FCC

RoHS

