

IPD35

LITE SERIES

IP INFRA RED DOME CAMERA



KEY FEATURES

- 1/2.8" Sony IMX323 CMOS Progressive Scan
- Indoor application
- High Definition resolution 1920×1080
- Support multiple resolution
- 3.6mm fixed lens
- Support ONVIF protocol interface
- 48 IR LEDs
- 30m IR range
- Support H.264
- Min illumination 0lux (IR LED)
- Low intensity of illumination sensor
- IR-CUT optical filter technology



Day & Nite



Infra Red

TECHNICAL SPECIFICATIONS

Image Sensor	1/2.8" Sony IMX323 CMOS Progressive Scan
Min. Illumination	0.01Lux @(F1.2,AGC ON), 0Lux with IR
IR Distance	30m
Shutter	Manual /Auto (Adjustable, 1/25~1/100000)
Lens	3.6mm, M12 mount
Day & Night	Auto (ICR) / Color / Black & White
Video Compression	H.264
Video Output Bitrate	128Kbps~8Mbps
Audio Compression	PCM/PCMA
Audio Output Bitrate	64Kbps(G.711) /16Kbps(G.726)
Max. Resolution	Mainstream: 1920×1080, Sub-stream: 720×576
Frame Rate	50Hz: 25fps(1920×1080), 60Hz: 30fps(1920×1080)
Alarm	Motion Detection Alarm
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,PPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6
Interface Protocol	ONVIF
General Function	Flicker Filter, Dual-stream, Mirror Image
Communication Interface	RJ45 (10M/100M Ethernet)
Working Temperature	-10°C~50°C
Power Supply	DC12V/POE

IMAGE SETTING

Brightness	Manual
Contrast	Manual
Saturation	Manual
Sharpness	Manual
Day / Night	Auto (ICR) / Day / Night
Mirror	Open / Close
Rotate Image	Open / Close
Wide Dynamic Range	Enable / Disable (Value 1 - 10)
Motion Detection	Yes
Video Masking	Yes
Image Source	50Hz / 60Hz