

IHP20M-PIR


HYBRID SERIES

AHD PASSIVE INFRA RED HIDDEN CAMERA



KEY FEATURES

- 1/2.8" 2.0Megapixels CMOS IMX322
- 1920×1080 HD resolution
- Control OSD menu via coaxial cable
- Support AHD/TVI/CVI/CVBS signal output
- 2DNR/3DNR
- Max. transmission distance up to 500 meters
- 3.7mm Fixed Pinhole Lens
- 0.01Lux (F1.2), 0 Lux with IR



TECHNICAL SPECIFICATIONS

Image Sensor	1/2.8" 2.0 Megapixels CMOS IMX322
Signal System	PAL/NTSC
Effective Pixel	1920H*1280V
Frame Rate	1920*1080@25fps,1920*1080@30fps
Min Illumination	0.01LUX/F1.2
Shutter	4/25s~1/45,000s
Lens	3.7mm Fixed Pinhole Lens
IR	No IR, distance reach 5~10m
Signal Type	AHD/TVI/CVI/CVBS optional
Transmission Distance	Over 500 meters with 75-3 coaxial cable
SNR	≥48DB
Work Environment	Temperature -20°C+60°C Humidity less 90% (non condensation)
Power	DC12V±10%

IMAGE SETTING

OSD	OSD menu via coaxial cable
White Balance	Auto
Exposure	Global exposure
Day & Night	Mode Switch
Noise Reduction	2DNR, 3DNR
WDR	Support
Others	Smart IR, contrast, brightness, sharpness, saturation, flip

