



CL-818

Proximity Time Recorder

Door Access Control

Companies that focus on increasing the overall productivity and efficiency of the organization will find this system a worthwhile investment and a valuable asset. With this system, "FRAUD" is not only reduced to a minimum as in the case of proxy or buddy punching, all previous methods of manual calculations of standard and overtime hours performed by employees will be a thing of the past. You will be able to enjoy up-to-date reports such as total standard/overtime hours performed by individual employees, late login and early logout by personnel and many others.

- ✦ CL-818 ADAPTS ARM9-200MHZ CPU, HIGH PERFORMANCE AND LOW POWER PLATFORMS
- ✦ THE QUALITY OF THE FINGERPRINT IDENTIFICATION IS IMPROVED OBVIOUSLY, IDENTIFICATION SPEED CAN REACH 7000-8000 PER SECOND
- ✦ THE ALGORITHM OF ARM9 VERSION HAS EVIDENT IMPROVEMENT ON RELIABILITY, PRECISION AND SPEED, IT CAN MANAGE 1500 FINGERPRINT TEMPLATES WITHIN 1 SECOND
- ✦ INNOVATIVE NEW IDEAL CHOICE FOR EVERY BUSSINESS APPLICATION LIKE OFFICE, FACTORY, HOTEL, HOSPITAL, BANK ETC.....
- ✦ DOOR ACCESS CONTROL CAPACITY : FOR LOCK OUTPUT AND DOOR MONITORING. IT CAN BE CONFIGURED TO LOCALLY CONTROL AND MONITOR A DOOR SECURING YOUR PREMISES.



Fully Touch Key Pad and Color Screen!



Technical Specification

- * User capacity : 30,000
- * Transaction storage : 200,000 Transaction
- * Resolution : 500dpi
- * Verification mode : 1:1 OR 1:N
- * Access : Proximity Card, Password
- * Identification speed : < 1sec
- * FAR : <0.0001%
- * FRR : <0.01%
- * Communication : RS232, RS485, TCP/IP, USB Host
- * Power consumption : <5W
- * Operation temperature : 0°C ~ 60°C
- * Operation humidity : 20%~60%
- * Size : 180(L) x 140(W) x 45(D) mm