



CL-928

Fingerprint Time Recorder

Companies that focus on increasing the overall productivity and efficiency of the organization will find this system a worthwhile investment and a valuable asset. With this system, "FRAUD" is not only reduced to a minimum as in the case of proxy or buddy punching, all previous methods of manual calculations of standard and overtime hours performed by employees will be a thing of the past. You will be able to enjoy up-to-date reports such as total standard/overtime hours performed by individual employees, late login and early logout by personnel and many others.



✦ CL-928 & CL-938 ADAPTS ARM9-200MHZ CPU, HIGH PERFORMANCE AND LOW POWER PLATFORMS

✦ THE QUALITY OF THE FINGERPRINT IDENTIFICATION IS IMPROVED OBVIOUSLY, IDENTIFICATION SPEED CAN REACH 7000-8000 PER SECOND

✦ THE ALGORITHM OF ARM9 VERSION HAS EVIDENT IMPROVEMENT ON RELIABILITY, PRECISION AND SPEED, IT CAN MANAGE 1500 FINGERPRINT TEMPLATES WITHIN 1 SECOND

✦ SUPPORTING FINGER 360 DEGREE IDENTIFICATION

✦ BATTERY BACKUP SYSTEM PROVIDING WHEN DURING POWER FAILURES. (OPTIONAL)

✦ INNOVATIVE NEW IDEAL CHOICE FOR EVERY BUSSINESS APPLICATION LIKE OFFICE, FACTORY, HOTEL, HOSPITAL, BANK ETC.....

✦ DOOR ACCESS CONTROL CAPACITY : FOR LOCK OUTPUT AND DOOR MONITORING. IT CAN BE CONFIGURED TO LOCALLY CONTROL AND MONITOR A DOOR SECURING YOUR PREMISES. (OPTIONAL)



Technical Specification

* User capacity	: 3000
* Transaction storage	: 60,000 Transaction
* Resolution	: 500dpi
* Active scan area	: 16 x 16mm
* Verification mode	: 1:1 OR 1:N
* Access	: Fingerprint , Password; Proximity Card (OPTIONAL)
* Backup Battery (Optional)	: Approx. 3~4 hours
* Identification speed	: < 1sec
* FAR	: <0.0001%
* FRR	: <0.01%
* Communication	: RS232, RS485, TCP/IP, USB Host
* Power consumption	: <5W
* Operation temperature	: 0°C ~ 60°C
* Operation humidity	: 20%~60%
* Size	: 180(L) x 140(W) x 45(D) mm