

CODE SOFT®

High Quality Thermal Printer
TP-3250H Thermal printer



TP-3250H series is the top-of-the-line printing solution of CODE SOFT. In particular, TP-3250H supports up to 68 international languages including simplified & traditional Chinese, Japanese, Korean; and built in 256K data buffer and 256K bytes NV flash memory, support receipt reprinting after paper roll replaced, support black mark location sensor, support Serial, USB and Ethernet port in one interface board; IP address can be altered by using Serial and USB port. TP-3250H features a drop-in paper loading system, easy to use for customers. And support COM port emulating USB, making serial port with high speed communication as USB, then realizing high speed printing but no need to change software. TP-3250H supports Windows X32, X64 and Linux driver, now widely applied for hospitality, retail, POS market, bank, taxation, post and exclusive shop.

Features

- **Faster network connection and printing, not more "Printing Missing"**
TP-3250H is built in 100M/10M Base/T network interface card which provides faster network connection and printing, eliminates delayed time and modifies the program to print out all the receipts, providing better compatibility for wider application.
- **Support WAN printing**
TP-3250H supports connection to Wide Area Network printing through LAN router.
- **Support Network Auto-reconnect after disconnect**
Support auto-connect function after network disconnects.
- **Support black mark sensor**
User can choose black mark location to be on the right, left, middle of the paper.
- **Built-in Web-IP tools**
User can change IP address, ID address, Gateway, sub-net mask, check printer status and get dynamic IP address through Web-IP automatically without installing the IP tools, providing more friendly operation interface.
- **Printer status monitoring**
 - Monitoring the top cover status, paper status, cutter faulty status and button status.
 - Monitoring the printing status, task competing status and pending task status.
 - Monitoring printer network connection status – ON or OFF by sending command.
- **Designed with waterproof, oil proof, dust-proof, and vermin-proof structure, much better for kitchen use.**



Retail



POS



Catering



Ticketing



All-in-one Serial, USB, Ethernet Interface

Specifications

- Both of Epson ESC/POS and STAR commands supported.
- 250mm/sec ultra high printing speed
- Front paper loading and paper exit
- Bar code printing
- 100mm large paper roll
- Paper width including 43mm, 58mm, 70mm, 80mm, 82mm
- All-in-one Serial, USB, 100M Ethernet interface
- Support IP change by using Serial or USB port
- USB-COM port emulation makes Serial port communication with high speed as USB
- Windows X32 / X64 / Linux / OPOS driver
- 256K data buffer and 256K NV Flash storage

Model	TP-3250H Specificaton
Print method	Direct thermal line
Dot density	576 dot/line or 512dot/line
Character	ANK character: Font A: 12×24dots Font B: 9×17dots Chinese: 24×24dots
Barcode type	UPC-A/UPC-E/JAN13(EAN13)/ JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128
Interface	All-in-one Serial, USB, Ethernet Interface
Print width	79.5±0.5mm
Paper diameter	100mm
Paper thickness	0.06~0.08mm
Power supply	DC 24V/2A
Auto cutter	full or partial
Reliability	100 Km
Work environment	Temperature: 0~45℃, Humidity: 10~80%
Storage environment	Temperature: -10~60℃, Humidity: 10~90%
Driver	Win 9X/Win ME/Win 2000/Win 2003/ Win NT/Win XP/Win Vista/Win 7, EPSON,SAMSUNG
Print speed	250mm/s
Kitchen printing	Support
Paper near end sensor	Support
Weight	1.90kg
Dimension	202x143 x144mm (LxWxH)

Authorize Distributor: