

The A4 'leader'

SureFlow™ Technology has been developed with the office user in mind. Leading edge technology has been incorporated into the H212 to allow you to laminate with confidence and ease. Stress free laminating at its best.

This laminator is the obvious choice of laminator for the discerning office.

The industry standard 241mm 'throat' caters for many sizes from small ID sized up to A4 size which is used for standard documents which you wish to protect and preserve.

Using 2x75mic (150 Total) pouches with this laminator you can extend the lifetime of your menus, reference documents etc. and for increased rigidity of document for items such as diplomas and certificates use 2x125mic(250Total) pouches.

Or if you want to carry our cold lamination this machine still meets your needs.

- **SureFlow™ Technology** simple and easy to use (2 x 'Heated Roller' Technology)
- Lamination width* from ID size to **A4 Max** (241 mm)
- Pouch capability – 2x 75mic (150 Total), 2x80mic (160 Total), 2 x 100mic (200 Total) & 2 x 125mic (**250 Total**) Micron
- Variable 'Hot' Temperature + 'Cold' setting
- Up to 65 A4's per hour capacity
- Carrier-free performance

Features & Benefits

- 1 SureFlow Technology-** designed to guide the pouch through the laminator and significantly reduce jamming
- 2 Simple stylish variable temperature guide:** Comprehensive control for users of all experience
- 3 Exit Tray-** Keeps the laminated product straight on exit minimising curling and warping
- 4 Auto switch off after 1 hour**
- 5 Only 5 minutes 'Warm up' period**
- 6 Release lever:** Function to solve any miss-feeding problems by releasing the document



Technical Specifications

Photo quality	Yes
Heat-up Time (75 mic)	5 min.
Speed mm/min.	330
Temperature control	Variable
Cold Lamination	Yes
Speed control	Fixed
Rollers	2
Max. Document size	A4 241 mm
Max. pouch thickness	2x125mic (250 Total)
Ready Light	Yes
Release Function	Yes

Pouch counter	-
Auto switch off	Yes, after 1 hour
Time to laminate 1	
Standard A4 Pouch	55 sec.
A4 Laminates / hr*	65
High Speed Pouches	
Laminates / hr*	No
Dimensions	400x173x117mm
Certification	GS / TÜV / CE
Weight	3.1 kg
Power Consumption	
Watts / Amps	500W/4A