

Panasonic

ideas for life

Compact Plain Paper Fax
with Copier
輕巧型普通紙傳真及影印機
KX-FP701ML

THERMAL TRANSFER / PLAIN PAPER

Strong Support for a Variety of Office Work!

- Navigator Key for Easy Operation
導航式瀏覽鍵
- 28-Page Document Memory
28頁文件記憶*1*2
- Enhanced Copier Functions
先進複印功能



Film Compatible
70m



Fast scanning
speed
saves time

Easy-to-read
2-line LCD screen

Simple operation of
various functions with
the Navigator Key

Versatile copier
functions meet
copying needs

Plain paper
convenience in a
compact design

Plenty of capacity
with a 28-page
document memory

TELECOMMUNICATIONS



Navigator Key for Easy Operation

The navigator key lets you easily control the volume and ringer level, as well as the volume and ringer level, as well as the functions.

導航式瀏覽鍵

用戶可利用導航式瀏覽鍵輕鬆地操控音量及鈴聲，更可用作控制來電話記憶及設定各項先進功能。



28-Page Document Memory*1*2

The system can store up to 28 pages in its built-in memory for transmission. Ideal for broadcasting multi-page documents to multiple locations. This feature will also allow the unit to receive documents up to 28 pages if it has run out of paper.

28頁文件記憶*1*2

可儲存多達28頁文件作記憶傳送及文件廣播傳送，而缺紙時接收記憶更高達28頁。



Enhanced Copier Functions

This fax provides you every copying feature you need, in one machine. The Enlarge (200/150%), reduce (92/86/72%), collate (sort), make up to 50 copies. Furthermore this fax performs a range of advanced copier functions.

改良影印機功能

本機備放大(200%或150%) / 縮小(92%、86%或72%) / 順序(分頁)等先進複印功能，更可複印多至50張副本。

Advanced Features

先進功能



Quick Scan

Spend less time waiting for your documents to scan! This feature rapidly scans a document into memory & then sends the document from memory to the recipient.

快速掃描功能

利用快速掃描功能把文件存於記憶內，傳真機便會自動傳送文件給對方，減少等候時間，方便快捷。



Sequential broadcasting (20 Locations)

The sequential broadcast feature allows you to send multi-page documents to multiple locations at your command.

文件廣播傳送功能(20個地點)

使用文件廣播傳送功能，用戶可把多份文件順序傳送至多個不同地方，而預選傳真號碼可多達20個。




Error Correction Mode (ECM)

The system ECM checks documents line by line during transmission. If it detects errors caused by line noise, it resends the same line to ensure good quality.

錯誤訊息修正模式

錯誤訊息修正系統能進行偵察傳送的文件，如發現訊息受干擾而導致錯誤，便會自動修正及補送正確訊息，確保文件以優質效果發送。



Informative 2-line LCD Screen

The 2 x 16 character LCD readout indicates operating modes, memory contents, clock time, and telephone number dialed. Also it helps during programming system features or storing telephone number in directory.

信息型雙行式液晶顯示屏

2 x 16 雙行式液晶顯示屏可顯示操作方式、記憶內容、時鐘時間和電話號碼。它也是編程系統特點或將電話號碼存入目錄的好幫手。

Other Features

其他功能

- Distinctive Ring detection*1
- 2-line LCD readout
- 64-level halftone resolution
- Polling function
- Friendly fax reception
- Extension line transfer
- 10-page Automatic document feeder
- 50-sheet paper tray
- 1-6 one-touch dialer
- Phonebook 100-station
- Electronic volume control
- Handset mute
- External telephone jack

Language

- LCD readout (Base): English
- Operation Panel: English

- 指定來電偵察功能*1
- 雙行式液晶顯示屏可顯示名稱及號碼
- 64級灰度調節
- 提取傳真功能
- 友善接收功能
- 分線轉接
- 10頁自動送稿器
- 可容納50張紙的載紙盤
- 1至6單觸式撥盤
- 100個電話簿記憶號碼
- 電子音量控制
- 手機靜音功能
- 外接電話控制

- 語言
- 液晶顯示可顯示名稱及號碼：英語
- 操作盤：英語

Specifications

規格

Facsimile		傳真	
Compatibility :	ITU-T G3	兼容性 :	ITU-T G3
Paper Handling :	A4	文件大小 :	A4
Scanning Width :	208 mm	掃描寬度 :	208毫米
Resolution :	Standard/fine/super fine/photo	解像度 :	標準 / 精細 / 超精細 / 照片
Halftone :	64 levels	灰度 :	64級
Modem Speed :	9.6 kbps	解調器速度 :	9.6kbps自動調節減速*1
Transmission Speed :	Approx. 12 sec/page*1	傳送速度 :	傳送每頁約12秒 *1
Compression System :	MH, MR, MMR	壓縮系統 :	MH / MR / MMR
Document Memory :	Max. 28 pages**2	文件記憶 :	接收記憶最多28頁**2
Print Method :	Thermal transfer on plain paper	打印方式 :	普通紙熱感傳真式
Ink Film :	70m(10m included film)	打印菲林 :	70米 (隨機附10米菲林卷)
Paper Capacity :	Max. 50 sheets (75 g/m2 paper)	紙盤容量 :	最多50頁
Automatic Document Feeder :	Max. 10 sheets	自動送稿器容量 :	最多10頁
Integrated Telephone System		綜合電話系統	
Dial Mode :	Tone (DTMF) / pulse	撥號方式 :	音頻DTMF / 脈衝式
Dialing Memory :	106 telephone numbers with name	撥號記憶 :	106 字符電話記憶
Power Source :	AC 220-240V, 50/60 Hz	交流電源 :	AC 220 - 240 V , 50/60 Hz
Dimensions (H x W x D):	18.5 cm x 35.5 cm x 27.2 cm	體積 (闊x深x高):	18.5 毫米 x 35.5 毫米 x 27.2 毫米
Weight :	3.5kg	重量 :	3.5 千克

*1 Based on ITU-T No. 1 test chart at standard mode.

*2 Max. 28 pages for out-of-paper reception. Max. 25 pages for memory transmission. ECM is not activated.

*3 Subscription to the Distinctive Ring service required.

Optional Accessories

KX-FA57E Replacement Film (70 m Ink Film roll)

*1 按 ITU-T No. 1 測試圖計算於標準模式計算。

*2 缺紙記憶最多為28頁，而文件傳送記憶最多為25頁。

*3 需配合電話公司所提供之有線收費服務使用，請向電話公司查詢。

消耗品

KX-FA57E 可更換打印菲林(70米墨水菲林卷)

Panasonic

http://www.panasonic.com.my